SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** *2016-02-22* **Version** *4*

1. IDENTIFICATION

Product identifier

Product name EQUIVIS XLT 15

Other means of identification

Product Code(s) 083887

Number PEN
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Hydraulic Fluid.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address
TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number
Company Phone Number +1 (908) 862-9300
Emergency telephone +1 866 928 0789 (24h/24, 7d/7)
+1 215 207 0061 (24h/24, 7d/7)

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization - Category 1
Aspiration toxicity - Category 1

Label elements

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

DANGER

May cause an allergic skin reaction
May be fatal if swallowed and enters airways

Precautionary Statements - Prevention
Avoid breathing dust/fume/gas/mist/vapours/ spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response
Specific treatment (see Section 4 on this label)
Skin
IF ON SKIN: Wash with plenty of soap and water
If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage
Store locked up

Precautionary Statements - Disposal
Dispose of contents/ container to an approved waste disposal plant

Unknown Acute Toxicity
No information available

Hazards not otherwise classified (HNOC)
None known

Other information

Physical-Chemical Properties	Contaminated surfaces will be extremely slippery.
Properties Affecting Health	No information available.
Environmental properties	Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Mixture

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	75-100
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	84605-29-8	< 1
Triphenyl phosphite	101-02-0	<0.1
Calcium sulfonate	61789-86-4	< 0.1
Butylated phenol	128-39-2	< 0.1
O,O,O-triphenyl phosphorothioate	597-82-0	<0.1
Alkylphenol	121158-58-5	<0.1
2-ethylhexanol	104-76-7	< 0.1

** The exact percentage (concentration) of composition has been withheld as a trade secret*

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice If symptoms persist, call a physician. Show this material safety data sheet to the doctor in attendance. Do not breathe dust/fume/gas/mist/vapors/spray. IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Consult a physician if necessary. Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.

Inhalation Move to fresh air. Consult a physician. If not breathing, give artificial respiration. Move to fresh air in case of accidental inhalation of vapors. Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.

Ingestion Do NOT induce vomiting. Rinse mouth. If symptoms persist, call a physician. If swallowed, call a poison control center or doctor immediately. Risk of product entering the lungs on vomiting after ingestion. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia. Never give anything by mouth to an unconscious person.

Protection of First-aiders Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Skin contact May cause an allergic skin reaction. Causes mild skin irritation.

Eye contact Avoid contact with eyes.

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways.

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Redness. Coughing and/ or wheezing. Difficulty breathing. Itching. Rashes.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Dry powder. Foam. Carbon dioxide (CO_2). Water spray. Cool containers / tanks with water spray. ABC powder.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Special Hazard Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Flash back possible over considerable distance. Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Vapor protective clothing with SCBA should be worn for large spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ensure adequate ventilation. Remove all sources of ignition. Heat, flames and sparks. Contaminated surfaces will be extremely slippery.

Other information See Section 12 for additional information.

Environmental precautions

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

General Information

Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. Prevention of fire and explosion. A vapor suppressing foam may be used to reduce vapors. Try to prevent the material from entering drains or water courses. Do not allow material to contaminate ground water system. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Local authorities should be advised if significant spillages cannot be contained. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use mechanical means such as pumps, skimmers and absorbent materials. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Prevent the formation of vapors, mists and aerosols. Do not eat, drink or smoke when using this product. There is a hazard associated with rags, paper or any other material used to remove spills which become soaked with product. Avoid accumulation of these: they are to be disposed off safely after use. Avoid static electricity build up with connection to earth. When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist.

Prevention of fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Design installations (machinery and equipment) to prevent burning product from spreading (tanks, retention systems, interceptors (traps) in drainage systems). OPERATE ONLY ON COLD AND DEGASSED TANKS IN VENTILATED PREMISES (TO AVOID RISK OF EXPLOSION). Do not use compressed air for filling, discharging or handling. Empty containers may contain flammable or explosive vapors.

Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended. Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Technical measures/Storage conditions	Keep container tightly closed in a dry and well-ventilated place. Keep in a bunded area. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep away from heat. Keep out of reach of children.
Materials to Avoid	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits	Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m^3, NIOSH (REL) TWA 5 mg/m^3, STEL 10 mg/m^3, ACGIH (TLV) TWA 5 mg/m^3 (highly refined).

Exposure controls

Engineering Measures	Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment

General Information	Protective engineering solutions should be implemented and in use before personal protective equipment is considered.
Eye/Face Protection	If splashes are likely to occur, wear:. Safety glasses with side-shields.
Skin and body protection	Wear suitable protective clothing. Protective shoes or boots.
Hand Protection	Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Hygiene measures

Regular cleaning of equipment, work area and clothing is recommended. Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Wash hands with water as a precaution. Avoid breathing vapors, mist or gas. Avoid prolonged and repeated contact with the skin, especially with used or waste product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color		red	
Physical State @20°C		liquid	
Odor		Petroleum distillates	
Odor Threshold		No information available	
Property	**Values**	**Remarks**	**Method**
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	**96 °C**		ASTM D 92
	205 °F		ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.860	@ 15 °C	ASTM D 1298
Density	860 kg/m^3	@ 15 °C	ASTM D 1298
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	~15 mm2/s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
Other information			
Specific Gravity	0.860	@ 15 °C	ASTM D 1298
Freezing Point		No information available	
Pour point	< -50 °C		ASTM D 97

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to Avoid Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents.

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Redness. Coughing and/ or wheezing. Difficulty breathing. Itching. Rashes.

Skin contact May cause an allergic skin reaction. Causes mild skin irritation.

Eye contact Avoid contact with eyes.

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity - Product Information

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Oral Not classified.

Dermal No information available

Inhalation Not classified

Acute toxicity - Component Information

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	LD50 3200 mg/kg (Rat - OECD 401)	LD50 > 2002 mg/kg (Rat - OECD 402)	
Triphenyl phosphite 101-02-0	LD50 1590 mg/kg (Rat - OECD 401)	> 2000 mg/kg (Rabbit) = 1180 mg/kg (Rat)	LC50 (1h) > 6.7 mg/l (Rat - aerosol - OECD 403)
Calcium sulfonate 61789-86-4	> 5000 mg/kg (Rat)	> 4000 mg/kg (Rabbit)	
Butylated phenol 128-39-2	> 5000 mg/kg (Rat)	= 10000 mg/kg (Rabbit)	
O,O,O-triphenyl phosphorothioate 597-82-0	LD50 > 2000 mg/kg (Rat)		
Alkylphenol 121158-58-5	LD50 2100 mg/kg (Rat)	LD50 15000 mg/kg (Rabbit)	
2-ethylhexanol 104-76-7	LD50 > 2000 mg/kg (Rat)	LD50 > 3000 mg/kg (Rat - OECD 402)	LC50 (4h) > 20 mg/l (Rat)

Sensitization May cause an allergic skin reaction. Contains sensitizer(s). May cause sensitization by inhalation and skin contact.

Carcinogenicity This product is not classified carcinogenic.

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	-	-		-

Mutagenicity This product is not classified as mutagenic.

Reproductive toxicity This product does not present any known or suspected reproductive hazards.

Aspiration Hazard May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life with long lasting effects

Acute aquatic toxicity - Product Information

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Distillates (petroleum), hydrotreated light naphthenic 64742-53-6		LC50 (96h) > 5000 mg/L Oncorhynchus mykiss ()	EC50 (48h) > 1000 mg/L Daphnia magna	

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	ErC50 (72h) 24 mg/l (Desmodesmus subspicatus - OECD 201)	LL50 (96h) 4.5 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) 23 mg/l (Daphnia magna - OECD 202)	
Triphenyl phosphite 101-02-0			EC50(48h) 0.94 mg/l (Cladocère)	
Calcium sulfonate 61789-86-4		LC50 (96h) 5.7-9.7 mg/L Pimephales promelas (static) LC50 (96h) 1.0-10.0 mg/L Pimephales promelas (semi-static)	EC50 (48h) 6.2 - 12 mg/L Daphnia magna	
Butylated phenol 128-39-2			EC50 (48h) = 0.45 mg/L Daphnia magna	
O,O,O-triphenyl phosphorothioate 597-82-0		LC50 (96h) < 100 mg/l (Fish)	EC50 (48h) > 100 mg/l (Daphnia magna)	
Alkylphenol 121158-58-5			EC50(48h) 0.037 mg/l (Daphnia magna)	
2-ethylhexanol 104-76-7	EC50 (72h) = 11.5 mg/l (Scenedesmus subspicatus)	LC50 (96h) 17.1 mg/l (Leuciscus idus)	EC50 (48h) = 39 mg/L Daphnia magna	

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Alkylphenol 121158-58-5		NOEC(21d) 0.0037 mg/l (Daphnia magna - semi static - OECD211)		

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information .

Chemical Name	log Pow

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts 84605-29-8	0.56
Triphenyl phosphite 101-02-0	6.62
O,O,O-triphenyl phosphorothioate 597-82-0	5.1
2-ethylhexanol 104-76-7	2.9

Mobility

Soil No information available

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Empty containers may contain flammable or explosive vapors. Do not burn, or use a cutting torch on, the empty drum. Empty containers should be taken to an approved waste handling site for recycling or disposal.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

15. REGULATORY INFORMATION

International Inventories

All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Alkylphenol	121158-58-5	<0.1		Group V		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

Unknown

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

Distillates (petroleum), hydrotreated light naphthenic 64742-53-6	X			

16. OTHER INFORMATION

NFPA	**Health Hazard** 1	**Flammability** 1	**Instability** 0	**Physical and chemical hazards** -
HMIS	**Health Hazard** 1	**Flammability** 1	**Physical Hazard** 0	**Personal protection** X

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)
Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2016-02-22
Revision Note *** Indicates updated section
Abbreviations, acronyms
ACGIH = American Conference of Governmental Industrial Hygienists
bw = body weight
bw/day = body weight/day
EC x = Effect Concentration associated with x% response
GLP = Good Laboratory Practice
IARC = International Agency for Research of Cancer
LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals
LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals
LL = Lethal Loading
NIOSH = National Institute of Occupational Safety and Health
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
NOEL = No Observed Effect Level
OECD = Organization for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material
Legend
Section 8
ACGIH - American Conference of Governmental Industrial Hygienists
OSHA - Occupational Safety and Health Administration
NIOSH - National Institute for Occupational Safety and Health
TLV - Threshold Limit Values
PEL - Permissible Exposure Limits
IDHL - Immediately Dangerous to Life or Health concentrations
TWA - Time Weight Average
STEL - Short Term Exposure Limits
S* - Skin notation
TSCA - Toxic Substance Control Act

SDS # : 083887

EQUIVIS XLT 15

Date of the previous version: 2016-02-22 **Revision Date:** 2016-02-22 **Version** 4

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above.It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk.The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity.The user bears sole liability for the precautions required when using the product.The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive.It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet