

MATERIAL SAFETY DATA SHEET

(Complies with 29 CFR 1910.1200)

PRODUCT NAME:

FUEL ETHANOL

ADM PRODUCT CODE:

017609

SYNONYMS:

Denatured Ethanol, Ethyl Alcohol - Denatured

CHEMICAL FORMULA:

C₂H₅OH

SECTION I

MANUFACTURER:

Archer Daniels Midland 4666 Faries Parkway Decatur, IL 62526

EMERGENCY NUMBER:

(800) 424-9300 Chemtrec (USA)

(217) 424-5200 ADM Corporate

INFORMATION:

(888) 371-4408 or (563) 244-5208

DATE:

April 2010

SECTION II Hazardous Ingredients/Identity Information

COMPONENTS:

	CAS Number	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	Volume
Ethanol (Ethyl Alcohol) 200 proof	0064-17-5			95-98%
Natural Gasoline	8006-61-9			2-5%
*Benzene	0071-43-2	1 ppm	10 ppm	<0.1%

^{*}A chemical known to the State of California to cause cancer

SECTION III - Physical/Chemical Characteristics

Boiling Point, °F 165-175 Reid Vapor Pressure, psi, 100°F 3.5 Vapor Density (Air = 1) at 172°F 1.6 0.79 Specific Gravity (H₂O=1) at 60°F Evaporation Rate (Butyl Acetate=1) 3.2

Solubility in Water

Completely miscible

Appearance and Odor

Clear, colorless liquid; characteristic odor

SECTION IV - Fire and Explosion Hazard Data

Flash Point (Method Used):

Minus 5°F, Tag Open Cup

Auto ignition temperature: Flammable Limits (LEL):

>689°F 3.3

Flammable Limits (UEL):

Extinguishing Media:

CO₂, dry chemical or water for small fires; polar solvent foam for large fires. Water is not effective until the alcohol contains approx. 80% water.

Special Fire Fighting Procedures:

Unusual Fire and Explosion Hazards:

Flammable liquid.

SECTION V - Reactivity Data

Stability: Stable

Conditions to Avoid: Avoid heat, sparks and open flames, excessive storage temperatures and/or open containers

Incompatibility (Materials to Avoid): Strong oxidizers

Hazardous Decomposition of By-products: Aldehydes, carbon monoxide.

Hazardous Polymerization: Will not occur

SECTION VI - Health Hazard Data

Routes of Entry: Inhalation, skin, ingestion

Health Hazards (Acute and Chronic): Unconsciousness; coma; respiratory failure and death. removes natural oils and fats from skin. Moderately toxic (LD50 >5 gm/kg).

Carcinogenicity:

NTP:

Not determined

IARC Monographs:

Not determined

OSHA Regulated:

Yes

Signs and Symptoms of Exposure:

May cause dizziness, loss of balance and coordination

Medical Conditions Generally Aggravated by Exposure: Not determined

Emergency and First Aid Procedures: If swallowed, do not induce vomiting. If inhaled, remove person to fresh air.

Give artificial respiration if breathing has stopped. Get immediate medical attention. If splashed in eyes or on skin, flush immediately with copious amount

of water.

SECTION VII - Precautions for Safe Handling and Use

Steps to be taken in Case Material is Released or Spilled: Eliminate all sources of ignition. Spills should be collected for disposal.

Waste Disposal Method: Do not allow to enter sewers where vapors may become ignited. Incinerate in a furnace where permitted under appropriate federal, state and local regulations.

Precautions to be taken in Handling and Storing: Keep away from heat, sparks and open flame. Keep container closed. Use with adequate ventilation.

Other Precautions: Use explosion proof electrical equipment and non-sparking tools. Ground electrical equipment.

SECTION VIII - Control Measures

Respiratory Protection:

Self-contained breathing air mask for high concentrations.

Ventilation: Protective Gloves: Local exhaust ventilation should be used; mechanical exhaust acceptable Rubber

Eye Protection:

Chemical splash goggles

Other Protective Clothing or Equipment: Eye bath, safety shower

Work/Hygienic Practices: Practice good housekeeping.

HMIS Hazard Rating Index

	15 Hazard Rating Index
· 3	HEALTH (Chronic effects) FLAMMABILITY
60	REACTIVITY
H	PROTECTIVE EQUIPMENT

NFPA D.O.T. Disposal

	HEALTH FLAMMABILITY
0.44	REACTIVITY
N/A	OTHER

SECTION IX - Transportation Information

U.S. Dept. of Transportation

U.S. Dept. of 1 rans	portation
ID Number	UN 1987
Proper Shipping Name	Alcohols, n.o.s.
	(Ethanol, gasoline)
Hazard Class	3
Packing Group	II
Label Statement	Flammable Liquid

Water Transportation

water I ransportation		
ID Number	UN 1987	
Proper Shipping Name	Alcohols, n.o.s. (Ethanol, gasoline)	
Hazard Class	3	
Packing Group	n	

The information in this data sheet does not constitute any contractual warrant as to product properties and is based on the current state of knowledge. For all chemical emergencies, call Chemtrec at 1-800-424-9300.